

MediaWall specification

From the office or boardroom, to conference, training or breakout rooms – James Tobias **MediaWall** applications are limitless.

LCD displays, drop down screens, dry wipe boards or flip charts: any media can be cleverly and discreetly hidden behind fascias and doors when not in use. Whether it's digital conferencing or traditional presentations, meetings never looked so slick. MediaWall maximises capacity, minimises floor space needs and puts technology front and centre.

DOORS

Full height doors are made to ceiling height (less 100mm), to a maximum ceiling height of 2,900mm, allowing for clean lines and up to 20% additional filing capacity.

Dual hardness PVC soft seal is used at meeting junctions between doors.

Standard finish is 18mm MFC with 1mm PVC edging.

Choose from 10 standard door styles, including glass doors.

Additional veneer and laminate styles are available on request.

SIDEWALL

18mm thick (MFC) light grey panels interlocked with aluminium reinforced columns.

All aluminium columns are punched every 25mm on a vertical grid, providing a fine tolerance for internal fittings adjustment.

All aluminium columns are punched every 100mm on a vertical grid, creating a separate, flexible grid for hinges and back brackets.

Dual hardness PVC soft seals on leading edges of aluminium columns provide dust and acoustic sealing against doors and partition back panels.

A unique clip design allows internals to be locked into aluminium columns without the need for tools.

STRUCTURAL SHELF

Supports the sidewalls on two rigid MDF beams for added strength.

Each base shelf features four levellers for maximum weight distribution and levelling prior to installing sidewalls.

Structural shelves are universal (top to bottom and back to front) to aid future relocatability.

REAR PANELS

Sturdy 8mm light grey panel.

Inner face of panels conceal all brackets for a clean finish.

Rear panel finish can match front doors, creating visually consistent dividing/partition wall.

END CLAD CLOAKING PANELS

An extensive range of end clad Cloaking Panels and wall abutment details are available.

Please ask for details.

IRONMONGERY

Hinges: Exposed knuckle, nickel-plated castings with 180° opening and built-in 'stay closed' functionality.

Locks: Lock and turn knobs in matt-brushed nickel finish, with integral removable barrel lock cylinder. Each lock is supplied with two keys. 'Flush' style locks are available as an alternative.

All locks are under a master series and can also be suited to order.

Standard locking includes 25 individual lock numbers (supplied randomly).

Keys: All keys are hinged to prevent damage to adjacent doors and to minimise chances of keys breaking in the lock barrel.

TRACK

Perimeter track at floor, ceiling and wall abutments provide height and width adjustment of +/-15mm.

All track is powder coated steel and can be matched to most RAL colours. Please ask for details.

INTERNAL FITMENTS

Light grey, powder coated steel fitments clip in to the aluminium column without the need for tools.

A complete range of fitments including combination filing shelves, slotted shelves, drawers, pigeon holes, filing frames and cradles are manufactured in-house. Please ask for details.

MODULE SIZES

Depth: 412mm, 472mm and 600mm

412mm depth for maximum space utilisation

472mm depth for to house computer print files and foolscap suspension files

600mm depth to accommodate hanging coats

Width: Double doors 800mm, 1,000mm and 1,200mm

Single doors 400mm, 500mm and 600mm